


## HP 9000 Series 700 Models 715/64, 715/80, and 715/100 Workstations



## HP Computer Museum www.hpmuseum.net

For research and education purposes only.



The HP 9000 Series 700 Models 715/64, 715/80, and 715/100 work-stations, based on the PA7100LC architecture, support the level of performance and functionality needed to meet the most demanding technical and commercial

customers' requirements. The Model 715s feature a new integrated color graphics subsystem as well as optional HCRX graphics accelerators. This winning graphics line-up provides industry-leading performance at a very low cost.

The Model 715s also boast new storage devices, such as 1GB and 2GB internal disk drives and support for the industry-standard 1.44MB 3.5" floppy drive.

Features	715/64	715/80	715/100	Benefits
CPU (PA-RISC 7100LC Processor) Bi-Endian switchable Built-in MPEG decompression				Supports current and future operating systems     Supports multimedia applications without
Clock frequency	64MHz	80MHz	100MHz	expensive, add-on hardware
• •	V 23/2222	0011111	2001/1212	
Performance Dhrystone 1.1 MIPS	78	97	122	
SPECint92	66.6	83.5	100.1	
SPECfp 92	96.5	120.9	137.0	
Linpack (100x100) MFLOPS(DP)	24.33	30.49	37.84	Computer
SPECrate_int92	1497.82	1866.06	2237.30	√Mus∋um
SPECrate_fp92	2281.39	2864.56	3225.85	
— <del>-</del>	2201.00	2004.00	0220.00	
Integrated Graphics Xmark93	6.55	7.90	8.63	. Londowship windowing and vocator newformance
Amarkes PLB93wire/PLBsurf93	43/16	7.90 52/20	61/23	Leadership windowing and vector performance
	1.4	1.8	1.6	
BD vectors (millions)	1.4 26			
Triangle per sec (000s)	-	32	40 23	
Lighted/shaded quads per sec (000s)	15	18	43	Visual effect of true color
8-plane color with HP Color Recovery technology				Visual effect of true color
HCRX Graphics	01.5	10.50	10.05	
Xmark93	91.5	10.72	12.25	<ul> <li>Leadership windowing and vector performance</li> </ul>
BD vectors (millions)	1.5	1.9	2.3	
Triangles per sec (000s)	26	32	40	
Lighted/shaded quads per sec (000s)	15	18	23	
PLB93wire/PLBsurf	45/21	57/26	62/29	Allows amouth movement of demania image
Double buffered + 8 overlay plane 24 plane (HCRX-24)				<ul> <li>Allows smooth movement of dynamic image</li> <li>16.7 simultaneous colors</li> </ul>
HCRX Graphics with Z buffering				High-performance hidden surface removal
PLB93wire/PLBsurf93	46/49	58/59	68/68	riight performance inductional defendance
Triangles per sec (000s)	270	340	410	High-performance 3D rendering
Lighted/shaded quads per sec (000s)	56	71	86	mga performance of rendering
CRX-48Z				
PLB93wire/PLBsurf93	N/A	N/A	68/69	Real-time rendering of large 3D models
Triangles per sec (000s)	N/A	N/A	600	<ul> <li>High-performance rendering allows manipulatio</li> </ul>
mangles per sec (000s)	IVA	IVA	000	of the largest models
Lighted/shaded quads per sec (000s)	N/A	N/A	140	of the largest models
Graphics Software				
X11/R6, PEX, PHIGS, Starbase, PowerShade				Speed and realism through standards
Monitors (multisync 1280 X 1024)	17" & 20"	17" & 20"	17" & 20"	Superb image quality and detail
` '	17 00 20	11 0.20	17 02 20	- Supero image quanty and detail
Memory and Cache	00.05CMD	90 05 CMD	99 95 CMD	I
Memory capacity Instruction/data cache (combined)	32-256MB 256KB	32-256MB 256KB	32-256MB 256KB	Improves application performance
	200ND	200KD	200KD	
Mass Storage	4/04 OD	4/04 CD	4/04 CD	A suid- unage of money at the second second
Internal/total disk capacity	4/84 GB	4/84 GB	4/84 GB	A wide range of mass storage options     A wide range of ranguable madis options
Removable storage	CD-ROM,	CD-ROM,	CD-ROM,	A wide range of removable media options
	floppy, DDS tape	floppy, DDS tape	floppy, DDS tape	•
Standard Interferen	DDO tape	DDO tape	DDO cape	,
Standard Interfaces				- Cupport for all common industry standard
IEEE 802.3, S/E SCSI-2, EISA (1), RS232 (2),				Support for all common industry-standard interfaces
Centronics (1), HIL and PS/2 (miniDIN) (2)				Multimedia capability
Audio I/O ports				- mannetia capability
_	IID IN A OF	IID IIV O OF	IID IIV O OF	Chandanda based as any transfer
Operating System	HP-UX 9.05	nr-ux 9.05	nr-ux 9.05	Standards-based operating system